



US007900336B2

(12) **United States Patent**
Akinwande et al.

(10) **Patent No.:** **US 7,900,336 B2**
(45) **Date of Patent:** **Mar. 8, 2011**

(54) **PRECISE HAND-ASSEMBLY OF MICROFABRICATED COMPONENTS**

(75) Inventors: **Akintunde Ibitayo Akinwande**,
Newton, MA (US); **Blaise Laurent**
Patrick Gassend, Cambridge, MA (US);
Luis Fernando Velasquez-Garcia,
Boston, MA (US)

(73) Assignee: **Massachusetts Institute of Technology**,
Cambridge, MA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 1358 days.

(21) Appl. No.: **11/404,676**

(22) Filed: **Apr. 14, 2006**

(65) **Prior Publication Data**

US 2009/0113687 A1 May 7, 2009

(51) **Int. Cl.**
B23Q 7/00 (2006.01)

(52) **U.S. Cl.** **29/559**; 29/281.5; 29/524; 200/11 D

(58) **Field of Classification Search** 29/25.35,
29/270, 760, 524, 505, 281.5, 559; 215/225
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,939,788	A *	2/1976	Schneible	425/6
4,038,504	A *	7/1977	McAnulty et al.	200/11 DA
4,406,376	A *	9/1983	Berghahn	215/224
4,444,326	A *	4/1984	Musel	215/209
5,129,531	A *	7/1992	Beck et al.	215/256
5,155,306	A *	10/1992	Iijima et al.	200/11 DA
5,312,456	A	5/1994	Reed et al.		
5,569,272	A	10/1996	Reed et al.		
5,676,850	A	10/1997	Reed et al.		
5,806,152	A *	9/1998	Saitou et al.	24/662
5,961,849	A	10/1999	Bostock et al.		

5,961,949	A	10/1999	Manev et al.		
6,039,195	A *	3/2000	Konefal et al.	215/209
6,143,293	A	11/2000	Weiss et al.		
6,408,120	B1	6/2002	Dautartas		
6,456,766	B1	9/2002	Shaw et al.		
6,457,873	B1	10/2002	Heier et al.		
6,612,450	B1 *	9/2003	Buono	215/228
6,647,036	B1	11/2003	Sun et al.		

(Continued)

OTHER PUBLICATIONS

Luis Fernando Velasquez-Garcia, The Design, Fabrication and Testing of Micro-fabricated Linear and Planar Colloid Thruster Array, Submitted to the Department of Aeronautics and Astronautics in partial fulfillment of the Degree of Doctor of Philosophy at the Massachusetts Institute of Technology, May 2004, pp. 73-74, 99-123, 164-185.

(Continued)

Primary Examiner — Lee D Wilson



Assistant Examiner — Jamal Daniel

(74) *Attorney, Agent, or Firm* — Sampson & Associates, P.C.

(57) **ABSTRACT**

A hand assembled MEMS apparatus includes meso-scale microfabricated components adapted for being moved by hand relative to one another from a loose-fit preliminary alignment orientation to a relatively tight-fit assembled orientation. A microfabricated spring member is integrally disposed on one of the components to bias the other component towards the assembled orientation. A cam surface disposed on the other component is configured to slidably engage and move the spring member against its bias upon continued hand movement in the assembly direction. A microfabricated abutment is disposed to limit relative movement of the components in at least one direction other than the assembly direction. A microfabricated tactile feedback member is configured to disrupt the hand movement in the assembly direction once the components have substantially reached the assembled orientation.

28 Claims, 13 Drawing Sheets



U.S. PATENT DOCUMENTS

6,756,540	B2	6/2004	Hedler et al.	
6,881,074	B1	4/2005	McLenaghan	
6,954,578	B2	10/2005	Chang	
7,010,854	B2	3/2006	Eldridge et al.	
7,462,789	B2 *	12/2008	Yamasaki et al.	200/11 DA
2008/0006604	A1 *	1/2008	Keady	216/83
2008/0116163	A1 *	5/2008	Sawyer	215/225
2009/0026363	A1 *	1/2009	Cheung et al.	250/282
2009/0026367	A1 *	1/2009	Cheung et al.	250/292
2009/0045038	A1 *	2/2009	Worones et al.	200/11 DA
2009/0113687	A1 *	5/2009	Akinwande et al.	29/270
2009/0189065	A1 *	7/2009	Hashimoto et al.	250/282

OTHER PUBLICATIONS

B. Gassend, L. F. Velasques-Garcia, A. L. Akinwande and M. Martinez-Sanchez, Mechanical Assembly of Electro Spray Thruster Grid, presented at the 29th International Electric Propulsion Conference (IEPC-2005-101), Princeton University, Oct. 31-Nov. 4, 2005, pp. 1-12.

N. Dechev, J. K. Mills, W. L. Cleghorn, Mechanical Fastener Designs for use in the Microassembly of 3D Microstructures, 2004 ASME International Mechanical Engineering Congress and RD&D Expo, Anaheim, California, Nov. 13-19, 2004, pp. 1-10.

E. E. Hui and S. N. Bhatia, Micromechanical Control of Cell-Cell Interaction, MTL Annual Research Conference 2006, 2006, 1 page.

M. Last, V. Subramaniam, K. S. J. Pister, Out of Plane Motion of Assembled Microstructures using a Single Mask SOI Process, Transducers 2005 conference, Jun. 5-9, 2005, pp. 684-687.

R. M. Bostock, J. D. Collier, R.-J. E. Jansen, R. Jones, D. F. Moore and J. E. Townsend, Silicon Nitride Microclips for the Kinematic Location of Optic Fibers in Silicon V-Shaped Grooves, Journal of Micromachining and Microengineering, 1998, pp. 343-360.

R. Prasad, K-F Bohringer, N.C. MacDonald, Design, Fabrication and Characterization of Single Crystal Silicon Latching Snap Fasteners for Micro Assembly, Proc. ASME Int. Mech. Eng. Congress and Exposition (IMECE'95), San Francisco, CA, Nov. 1995, 7 pgs.

Hongtao Han and Lee E. Weiss and Michael L. Reed, Micromechanical Velcro, Journal of MicroElectroMechanical Systems, 1 (1), Mar. 1992, pp. 37-43.

Alexis Christian Weber, Precision Passive Alignment of Wafers, Submitted to the Department of Mechanical Engineering in Partial Fulfillment of the Requirements for the Degree of Master of Science in Mechanical Engineering at the Massachusetts Institute of Technology, Feb. 2002, pp. 1-102.

* cited by examiner




FIG. 1
(PRIOR ART)




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5




FIG. 6




FIG. 7B




FIG. 7A

μ QMS ROD GRIPPER PROCESS FLOW (WAFERS TOP, UPPER BOTTOM)




FIG. 8A




FIG. 8B

μ QMS ROD GRIPPER PROCESS FLOW (WAFER LOWER BOTTOM)




FIG. 8C




FIG. 8D

PRECISE HAND-ASSEMBLY OF MICROFABRICATED COMPONENTS

GOVERNMENT SPONSORSHIP

This invention was made with government support under Contract Numbers FA9550-04-C-0118 and FA9650-05-C-0049, awarded by the Air Force, Contract Number W911QY-05-1-0002, awarded by the Army, and Contract Number N66001-04-1-8925, awarded by the Navy. The government has certain rights in the invention.

TECHNICAL FIELD

This invention relates to microfabricated components, and more particularly to meso-scale micro-fabricated components configured for hand-assembly while maintaining precision.

BACKGROUND INFORMATION

Throughout this application, various publications, patents and published patent applications may be referred to by an identifying citation. The disclosures of the publications, patents and published patent applications referenced in this application are hereby incorporated by reference into the present disclosure.

Microfabrication techniques, such as photolithography commonly used in the microelectronics industry to produce microprocessors and memory chips, have been increasingly used to fabricate other types of products, such as MEMS (Micro Electro-Mechanical Systems) devices and the like. These techniques advantageously enable the production of increasingly miniaturized devices, for use in products of ever decreasing size.

Those skilled in the art will recognize that these microfabrication techniques are particularly well suited to the production of relatively small, monolithic, two-dimensional (2-D) devices, due to their precise, deposited-layer fabrication approach. However, the inherent two-dimensionality of microlithography, in combination with the limited depth of vision associated with the small wavelengths necessitated by its micrometer precision capability, tends to militate against its use for relatively large (meso-scale) 3-D assemblies. This phenomenon thus effectively precludes the production of devices having larger aspect ratios, and/or larger out-of-plane dimensions. This microfabrication approach also tends to be ill-suited for larger, meso-scale devices in general, due to the increasing complexity associated with designing 3-D features for nominally microlithographic 2-D fabrication. In addition, as these devices become larger and more complex, there tends to be greater opportunity for generally incompatible process steps and/or parasitic errors, etc.

One attempt to address these concerns includes the microfabrication of discrete components, which are subsequently fastened to one another. This approach provides for the possibility of effectively isolating incompatible process steps to separate components, while also enabling the fabrication of larger, 3-D assemblies. Disadvantageously, however, it tends to be difficult to join these discrete components with the same level of precision (e.g., micrometer level), to which the components themselves are fabricated. As such, the components are either joined with less precision, which may defeat the purpose of using such a precise fabrication approach in the first place, or substantial costs may be incurred through the use of high precision assembly systems.

Micro-machined clips have been used to align and hold optical fibers, to position structures perpendicular to the substrate and as general purpose in-plane fasteners. LEGO-like systems to align and bond wafers for packaging have been proposed. Others have proposed micro-mechanical Velcro to mechanically bind wafers, without providing for relative positioning of the wafers. However, these approaches tend to either require complex assembly equipment, or result in relatively high assembled misalignments. (See, e.g., Bostock, et al., "Silicon Nitride Microclips for the Kinematic Location of Optic Fibers in Silicon V-Shaped Grooves", *Journal of Micro-mechanics and Microengineering*, Vol. 8, 1998, pp. 343-360. Last, et al., "Out of Plane Motion of Assembled Microstructures using a Single-Mask SOI Process," *Proc. 13th International Conference on Solid-State Sensors, Actuators and Microsystems*, IEEE, New-York, June 2005. Prasad, et al., "Design, Fabrication, and Characterization of SCS Latching Snap Fasteners for Micro Assembly," *Proc. ASME International Mechanical Engineering Congress and Exposition (IMECE)*, ASME, New-York, November 1995. Lee, et al., "A Morphology-Independent Wafer Level Rivet Packaging with Lego-Like Assembly," *Proc. 13th International Conference on Solid-State Sensors, Actuators and Microsystems*, IEEE, New-York, June 2005. Han, et al., "Micromechanical Velcro," *Journal of MicroElectroMechanical Systems*, Vol. 1, No. 1, March 1992.)

A need, however, exists for an assembly approach and system capable of enabling discrete, high-precision microfabricated components to be easily hand-assembled without substantial loss of precision.

SUMMARY

In one aspect of the present invention, a hand assembled MEMS apparatus includes meso-scale first and second components, at least one of which is microfabricated, and which are adapted for being moved by hand relative to one another in an assembly direction from a relatively loose-fit preliminary alignment orientation to a relatively tight-fit assembled orientation. A microfabricated spring member is integrally disposed on one of the first and second components, and configured to bias the other component towards the assembled orientation. A cam surface integrally disposed on the other component is configured to slidably engage and move the spring member against its bias upon continued hand movement in the assembly direction. A microfabricated abutment disposed on one of the components is disposed to limit relative movement of the components in at least one direction other than the assembly direction. A microfabricated tactile feedback member is configured to disrupt the hand movement in the assembly direction once the components have substantially reached the assembled orientation.

In another aspect of the invention, a method for fabricating a hand assemblable apparatus includes providing a meso-scale first and second components, at least one of which is microfabricated. The components are adapted for being moved by hand relative to one another in an assembly direction, from a relatively loose-fit preliminary alignment orientation to a relatively tight-fit assembled orientation. A microfabricated spring is integrally disposed on one of the components to bias the other component towards the assembled orientation. A cam surface is integrally disposed on the other component to slidably engage and move the spring member against its bias upon continued hand movement in the assembly direction. A microfabricated abutment is disposed to limit relative movement of the components in at least one direction other than the assembly direction. A

microfabricated tactile feedback member is disposed on at least one of the components to disrupt the hand movement in the assembly direction once the components have substantially reached the assembled orientation.

In a still further aspect of the invention, a hand assembled MEMS apparatus includes microlithographic, meso-scale first and second components adapted for being moved relative to one another in an assembly direction, and a microlithographic spring member integrally disposed on one of the components to bias the other component towards an assembled orientation. A microlithographic cam surface is integrally disposed on the other component to move in a rotational assembly direction to slidably engage and move the spring member against its bias. A plurality of microlithographic abutments disposed on at least one of the components is disposed to limit movement of the components relative to one another in at least one direction other than the rotational assembly direction. A microlithographic tactile feedback member disposed on at least one of the components is configured to disrupt movement in the assembly direction once the components have substantially reached the assembled orientation.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other features and advantages of this invention will be more readily apparent from a reading of the following detailed description of various aspects of the invention taken in conjunction with the accompanying drawings, in which:

FIG. 1 is an elevational, cross-sectional schematic view of an electrospray thruster of the prior art;

FIG. 2 is a plan view, with portions broken away, of a generalized electrospray thruster fabricated in accordance with an embodiment of the subject invention;

FIG. 3 is a perspective, cross-sectional view taken along 3-3 of FIG. 2;

FIGS. 4A-4C are views similar to that of FIG. 2, during various steps in the assembly thereof;

FIG. 5 is a series of simplified, cross-sectional views taken along 3-3 of FIG. 2, of various steps in the fabrication of the embodiment of FIGS. 3-4C;

FIG. 6 is a perspective view of an alternate embodiment of the subject invention;

FIG. 7A is a plan view, on an enlarged scale, with portions broken away, of a portion of the embodiment of FIG. 6;

FIG. 7B is a plan view, on a further enlarged scale, of a portion of the embodiment of FIG. 7A; and

FIGS. 8A-8D are a series of simplified, cross-sectional views taken along 8-8 of FIG. 7B, during various steps in the fabrication of the embodiment of FIGS. 6-7B.

DETAILED DESCRIPTION

In the following detailed description, reference is made to the accompanying drawings that form a part hereof, and in which is shown by way of illustration, specific embodiments in which the invention may be practiced. These embodiments are described in sufficient detail to enable those skilled in the art to practice the invention, and it is to be understood that other embodiments may be utilized. It is also to be understood that structural, procedural and system changes may be made without departing from the spirit and scope of the present invention. The following detailed description is, therefore, not to be taken in a limiting sense, and the scope of the present invention is defined by the appended claims and their equivalents. For clarity of exposition, like features shown in the

accompanying drawings shall be indicated with like reference numerals and similar features as shown in alternate embodiments in the drawings shall be indicated with similar reference numerals.

Briefly, embodiments of the present invention include apparatuses and approaches for fabricating high-precision MEMS (Micro Electro-Mechanical Systems) components which may be assembled into similarly precise meso-scale assemblies using low-precision hand assembly techniques. The individual components are fabricated using conventional microfabrication (e.g., microlithographic) techniques, and include a series of springs and fixed features that effectively self-locate into precisely defined orientations upon mating. The components may thus be assembled to levels of precision within the same order of magnitude (i.e., tens of microns or less in a given dimension) commonly provided by the microfabrication techniques themselves. This approach thus enables the microfabrication of devices which otherwise may not otherwise be capable of microfabrication, e.g., due to relatively large component size, aspect ratios, and/or parasitic errors, etc. These embodiments include provision for tactile feedback to the hand-assembler to avoid over-tightening or otherwise damaging the components during assembly.

At least two distinct embodiments are disclosed, which respectively use: 1) pure rotary motion; and 2) a combination of linear/rotary, or screw-type motion.

Embodiments of this invention thus involve more than merely a reduction in size of conventional macro-scale assemblies. Rather, the idea of using particularly precise microfabrication techniques to produce components that are then to be connected using imprecise hand assembly techniques, tends to be counter-intuitive. Also, the inherent two-dimensionality of conventional microfabrication techniques, in combination with the limited depth of vision associated with the small optical wavelengths necessitated thereby, tends to teach away from their use for relatively large (meso-scale) 3-D assemblies.

Where used in this disclosure, the term "meso-scale" refers to nominally hand-holdable or hand-sized components, namely, those having at least one dimension within a range of about 0.5 to 10 cm or more, to facilitate hand manipulation and/or hand assembly. The term "microfabrication" refers collectively to technologies used to fabricate components on a micrometer-sized, or micrometer-toleranced scale, including conventional micromachining, semiconductor processing, microelectronic fabrication, semiconductor fabrication, microlithography, MEMS fabrication, and integrated circuit fabrication technologies. Microfabrication thus includes those technologies commonly used on silicon wafers, glass, plastics, and the like, to fabricate integrated circuits, microsensors, inkjet nozzles, flat panel displays, laser diodes, compact discs, etc., and may also include techniques such as electro-discharge machining, spark erosion machining, laser drilling/cutting, and imprinting, casting and molding, etc. The term "axial" or "longitudinal" when used in connection with an element described herein, refers to a direction relative to the element, which is substantially parallel to its axis of rotation during assembly as shown and described herein. Similarly, the term "transverse" refers to a direction other than substantially parallel to the axial direction.

Referring now to the Figures, embodiments of the present invention will be more thoroughly described. Aspects of these embodiments may be applied to nominally any type of multiple-component microfabricated device. For ease of description, these aspects will be described with respect to two particular devices chosen to demonstrate the aforementioned

5

pure rotational, and screw-type assembly motions. These exemplary devices include a generalized electro-spray thruster, and a generalized linear quadrupole, with the understanding that the teachings hereof may be applied to nominally any other devices without departing from the spirit and scope of the invention.

Turning now to FIG. 1, electro-spray thrusters **20** have been investigated for use in the propulsion of various devices, such as earth orbiting satellites and other types of spacecraft. In these devices, an electrostatic field is used to extract ions or charged droplets from a liquid placed at the tip of needles (electrode) **22**. Typically kilovolt potential differences are required to startup and run the thruster, to generate thrusts of micronewtons or less per needle. In order to increase thrust levels, arrays of needles **22** must be used. Microfabrication techniques are well suited to producing such arrays with relatively high needle densities.

In order to maximize the packing density of needles in the array, precise alignment between the needles **22** and the holes **24** in the extractor grid **26** is needed. Due to their geometries and discrete functions, it is desirable to fabricate the electrode/needle array **22** and grid **26** as discrete components. These components may be fastened to one another with the desired alignment precision using wafer bonding techniques. However, these techniques involve relatively high temperatures and disadvantageously add complexity in the fabrication process.

Turning now to FIGS. 2 & 3, an exemplary embodiment of the present invention is shown and described in the form of a generalized grid **126** and electrode **122**, with various features, such as the needles, etc., omitted for clarity. As shown, this embodiment demonstrates a microfabricated MEMS assembly **120** in which a meso-scale first component, e.g., in the form of a grid **126** having a transverse dimension D_1 of about 2.5 cm, and a meso-scale second component, e.g., in the form of a grid support (electrode) **122** having a transverse dimension D_2 of about 4.5 cm, are microfabricated separately, to precise micrometer level tolerances, and then assembled using relatively low-precision manual assembly techniques, while maintaining high assembled precision.

The grid support **122** includes a series of spring fingers **128** disposed in spaced relation about the periphery of a recess **130** disposed therein. The recess **130** is sized and shaped to receive grid **126** therein, between fingers **128**. Moreover, recess **130** is sized and shaped so that an individual (i.e., the assembler) hand assembling the components, initially need only place grid **126** into loose-fitting orientation therein as shown. This loose-fitting orientation may typically be several orders of magnitude less precise than the assembled precision as discussed below.

Grid **126** includes a first set of cam surfaces **131** configured for an intermediate fit between respective abutments **133**. During rotational operation, one or more of the cam surfaces **131** may slidably engage their respective abutments **133** to cam the grid towards its centered orientation.

Grid **126** also includes a second set of cam surfaces **132** disposed to engage distal ends **138** and **140** of fingers **128** during the assembly of the grid, to move spring members **128** against their bias, as will be discussed in greater detail hereinbelow. A plurality of microfabricated (e.g., microlithographic) abutments **134** & **136**, respectively form leading and trailing edges of notches disposed within cam surfaces **132**. During rotation of the grid, the bias of the fingers **128** will drop distal ends **138**, **140** thereof into the notches. Engagement of distal ends **138**, **140** with the trailing edge abutments **136** serves to disrupt the rotational movement of grid **126** to provide tactile feedback during assembly, as will be discussed

6

hereinbelow. Similarly, engagement of the distal ends with the leading edge abutments **134** serves to restrict motion in the reverse rotational (i.e., the disassembly) direction. The grid **126** and grid support **122** also include mutually opposed stops **142**, **144**, which serve to prevent excessive rotation in the disassembly direction.

Turning now to FIGS. 4A-4C, assembly operation of this embodiment is described. Grid **126** may be assembled onto grid support **126** by initially placing grid **126** into loose-fitting orientation (e.g., with millimeter scale clearance) within recess **130** as shown in FIG. 4A. The assembler may then rotate the grid in the assembly direction (e.g., counterclockwise in the embodiment shown). As the grid rotates, the cam surfaces may engage abutments **133** to align the grid **126** to an intermediate clearance/alignment position (e.g., within about 50 μm of the center of the recess **130**), as shown in FIG. 4B. Upon continued rotation, cam surfaces **132** will engage distal ends **138**, **140** of spring fingers **128**, to flex the fingers against their bias.

It should be noted that the fingers **128** are relatively long and slender (e.g., having a length of about 1 cm, and a width of about 500-1000 μm in many embodiments), which provides the relatively brittle microfabricated structure with the desired flexibility, albeit at the expense of relatively high fragility. As such, fingers **128** tend to be delicate, and susceptible to breakage, particularly as a result of over-extension during hand assembly. For example, in particular embodiments in which the fingers **128** are between about 700 and 1000 μm wide, they are flexible, but may only tolerate a few hundred micrometers of deflection. These embodiments have thus been provided with various provisions for protecting them from accidental damage. One such provision includes placement of the fingers on the grid support **122**, where they tend to be better sheltered than they would be on the periphery of the grid **126**. This helps to protect them until assembly time.

In addition, as discussed above, when the grid **126** is first placed within the grid support **122** (FIG. 4A), the assembler need only place it in a relatively loose-fitting alignment (e.g., within about 0.5 to 1 mm of its intended location in meso-scale embodiments requiring an ultimate locational accuracy of tens of micrometers) for it to fall into the same plane as grid support **122**. From this position, the grid **126** may be wiggled around without risk to the fingers **128**, as grid stops (abutments) **133** prevent it from coming into contact with the fingers. Fingers **128** are thus protected from overextension by the interaction of cam surface **131** and abutment **133**, which helps to prevent excessive misalignment of the components, particularly once grid **126** has been rotated far enough to engage the fingers. Further protection from overextension is provided by finger stops **142**, formed as a wall portion of support superposed with distal ends **138** of the fingers, and by finger stops **144** formed as medial portions of fingers superposed with distal ends **140** of the fingers. These finger stops **142**, **144** thus serve as additional means for avoiding overextension of the fingers, such as due to rough handling during component assembly. Finally, redundant fingers **128** are provided in the event some fingers do break.

Referring now to FIG. 4C, rotation of grid **126** is continued in the assembly direction, which serves to slide distal ends **138**, **140** further along cam surfaces **132** until they drop, under the bias of the fingers, into the notches formed by leading and trailing abutments **134**, **136**, respectively. As mentioned hereinabove, this engagement with trailing abutments **136** disrupts the rotational movement of grid **126** to provide tactile feedback alerting the assembler that the fully assembled orientation has been reached. Similarly, engage-

ment of the distal ends with the leading edge abutments **134** serves to restrict motion in the reverse rotational (i.e., the disassembly) direction, i.e., to help maintain grid **126** and grid support **122** in their assembled positions. The grid **126** and grid support **122** also include mutually opposed stops **142**, **144**, which serve to prevent excessive rotation in the disassembly direction.

Once assembled, the grid **126** is firmly held in place by the relatively high axial stiffness of the microfabricated fingers **128**. The lateral flexibility of the fingers allows the assembly to accommodate differential thermal expansion of the components or portions thereof, or consistent over/under-etching of the side-walls during processing. Moreover, as mentioned above, this assembly approach enables the processes and material selection used to fabricate the grid **126** and the grid support **122** to be decoupled from one another. For example, temperature sensitive materials such as PTFE (Teflon®, DuPont) may be placed between grid **126** and support **126** without being damaged during fabrication/assembly (this is not possible, for example, with many conventional microfabrication techniques such as fusion bonding). Similarly, materials of one of the components may be altered without making similar alterations to the other component.

Having described embodiments of the present invention, the following is a description of the fabrication thereof. An exemplary process may require only three photo-masks: one for the alignment marks that appear on the device, one to describe the recess to be etched in the bottom wafer, and one to delineate the grid and grid support portions on the top wafer. In the embodiment shown, since the grid **126** fits into empty space within the grid support **126**, the grid **126** and portions **158** of grid support **122** may be combined on a single mask.

Referring now to FIG. 5, exemplary fabrication begins with double side polished (e.g., 650 μm thick) silicon wafers **150**. An oxide **152** is grown to protect the wafers from surface scratches which may prevent subsequent bonding. Alignment marks **154** are successively patterned on both sides of each wafer (step 1). The alignment marks may be patterned by spinning a thin photo-resist on both sides of the wafer, and exposing the sides to an alignment mark mask. After development, a buffered oxide etchant (BOE) is used to etch through the oxide at the unmasked points at the alignment mark locations. A chlorine-based plasma treatment may then be used to blacken the underlying silicon to form the marks **154**. The photo-resist may then be stripped using an oxygen plasma and a piranha ($\text{H}_2\text{O}_2/\text{H}_2\text{SO}_4$ 1:3) bath. After this initial preparation step, the wafers are separated into tops **156** and bottoms **157**, which undergo separate processing.

The top wafer **156** is selectively etched to form fingers **128** in portions **158**, and is then etched through, e.g., with Deep Reactive Ion Etching (DRIE) to separate portions **158** (of grid support **122**) from grid **126** (step 2a). In particular embodiments, it is desirable to obtain the straightest possible side-walls for the grid **126** and fingers **128**, since as discussed above, it is the contact between the two that determines the precision of assembly. For this reason, an aluminum etch mask **160** may be used when DRIE etching the top wafer **156**, since aluminum is not measurably etched by the DRIE process. By using it (e.g., in combination with a thin photo-resist) instead of thick photo-resist, those skilled in the art will recognize that one may obtain better feature transfer from the optical mask, and avoid taper caused by resist thinning near the edge of features. This may be accomplished by sputtering a layer of aluminum **160** (e.g., 0.2 μm thick) and then applying a thin photoresist thereon, which may then be patterned with the desired shape of the grid **126** and grid support por-

tions **158** and fingers **128**, etc. The aluminum is etched with aluminum etchant pan etch, and the underlying oxide with BOE. DRIE may then be used to etch through the wafer.

A recess is DRIE etched in the bottom wafer (step 2b), to form recesses below the fingers to prevent the fingers **128** (FIG. 4A-4C) from bonding to the bottom wafer **157**. The wafers are cleaned (e.g., with an oxygen plasma and piranha) and the protective oxide stripped (e.g., with hydrofluoric acid (HF)). The alignment marks **154** of portions **158** are then aligned with those of bottom wafer **157** and then fusion bonded to one another (step 3). The completed devices are ready for hand assembly of the grid **122** (step 4).

Referring now to FIGS. 6-8D, an alternate embodiment of the present invention is shown as a linear quadrupole assembly **220**. Those skilled in the art will recognize that linear quadrupoles are devices commonly used to filter species based on their specific charge, and are often used in mass spectrometry. Depending on the stability region where they operate, linear quadrupoles may require electrode aspect ratios as large as 60 or more to be able to resolve light ions (20 amu or less) with good resolution (1% or better). The resolution and ion transmission of these devices is greatly influenced by the misalignment in the relative positions of the rods (electrodes) **226**, as well as its taper.

Assembly **220** is a MEMS device that uses electrodes **226** having aspect ratios of 60 or more, and diameters down to 500 micrometers. This assembly **220** uses a system of meso-scaled DRIE-patterned springs **228** that allow a hand-assembled alignment precision of within about 5-20 micrometers or less. The precision of the diameter of electrodes **226** is also about 5 micrometers or less. Advantages of this quadrupole concept over prior approaches is its manual assembly, and that the rods **226** may be mounted and dismounted as desired, making the same "spring head" (support) component **222** (MEMS structure that includes the meso-scaled springs **228**, whose function is to grab, align and lock the electrode rods) reusable with different aspect ratios to be able to perform under different conditions of pressure, voltages, frequencies, etc.

This embodiment thus demonstrates another microfabricated MEMS assembly in which a meso-scale first component (electrodes/rods) **226** (e.g., having a length of within about 0.5 to 5 cm, and a diameter of about 0.5 mm), and a meso-scale second component (e.g., spring head support **222** having a transverse dimension D_1 (FIG. 7A) of about 0.7 to 0.8 cm) are microfabricated separately, to precise dimensional tolerances, and then assembled using relatively low-precision manual assembly techniques, while maintaining microfabrication-level assembled precision.

Referring now to FIG. 6, assembly **220** includes spring head component **222** which supports a series of hand assembled meso-scale stainless steel rods **226** (one shown). As also shown in this Figure, a series of (four) columns **227** are spaced about each rod **226**. These columns **227** can be made larger than the rods **226**, and therefore can provide additional structural support and enhance the precision of the assembly. These columns **227** may be assembled in the same manner as the rods **226**, and thus will not be discussed in detail.

Turning now to FIGS. 7A & 7B, spring head support **222** includes a series of spring fingers **228** disposed in spaced relation about a series (e.g., four as shown) of cavities **230** disposed therein. The cavities **230** are disposed about a central, active area **231** of the quadrupole, and are each sized and shaped to receive a rod **226** therein, between microfabricated (e.g., microlithographic) spring fingers **228** and microfabricated (e.g., microlithographic) stationary abutments **233**.

Each cavity **230** is sized and shaped so that an individual (i.e., the assembler) hand assembling the components, initially need only place rod **226** into loose-fitting orientation therein, whereupon a cam surface **232** (FIG. **8D**) disposed on rod **226** will engage fingers **228**.

This loose sliding fit enables the rod **226** to be easily placed by hand into a cavity **230**, with cam surfaces **232** initially clearing or sliding past abutments **233** and distal ends of fingers **228**. Upon continued insertion, such as coupled with a twisting rotational motion about its longitudinal axis, cam surface **232** may slidably engage distal ends of fingers **228**, to move spring members **228** against their bias, which serves to press the rod against abutments **233**. Abutments **233** thus serve to limit movement of the rods in a direction substantially transverse to the insertion (i.e., longitudinal) direction of the rods.

In addition, a microfabricated abutment **234** forms a ledge disposed at the bottom of each cavity **230**. During continued twisting insertion, the leading end of rod **226** will engage abutment **234**, which serves as a microfabricated tactile feedback member to disrupt continued movement in the insertion direction. This tactile feedback alerts the assembler that the fully assembled orientation of components **226** and **222** has been reached. This tactile feedback helps prevent damage that may otherwise be occasioned by the assembler continuing to apply force in the insertion direction after the fully assembled position has been reached.

As with the other embodiments discussed herein, fingers **228** tend to be delicate, and susceptible to breakage, particularly as a result of over-extension during hand assembly, due to their microfabricated structure and relatively small width (e.g., about 300 to 500 μm) and long length (e.g., about 5 to 8 mm) in many embodiments. The fingers **228** are relatively long and slender, which provides the relatively brittle microfabricated structure with the desired flexibility, albeit at the expense of relatively high fragility. For example, in this embodiment, while the fingers **228** are flexible, they may only tolerate a few tens of micrometers of deflection. Thus, in particular embodiments, fingers **228** have been placed on support **222**, between microfabricated layers to protect them from damage.

In addition, as best shown in FIG. **7A**, at least two fingers **228** are associated with each cavity **230**, to apply bias to each rod **226** in two mutually orthogonal directions, respectively towards two spaced abutment portions **233**. These orthogonal biasing directions are provided by forming each pair of fingers **228** with mutually orthogonal moment arms **229** as shown. Once assembled, the rods **226** are firmly held in place by the bias of the microfabricated fingers **228**, with the precision of the assembly being determined by the precision of the components (e.g., location of abutments **233** and diameter of rod **226**), rather than on the accuracy of assembly. The lateral flexibility of the fingers provided by their relatively long moment arms allows the assembly to accommodate differential thermal expansion of the components or portions thereof, or consistent over/under-etching of the side-walls during processing, while maintaining the rods in precise relative orientation. Moreover, as mentioned above, this assembly approach enables the processes and material selection used to fabricate the rods **226** and the support **222** to be advantageously decoupled from one another.

Turning now to FIGS. **8A-8D**, the following is a description of a representative fabrication approach for assembly **220**. As best shown in FIG. **8D**, the embodiment shown includes four micro-fabricated layers, i.e., a top **260**, middle **262**, upper bottom **264** and lower bottom **266**. (The terms

'top' and 'bottom' are merely used for convenience, and may be reversed without departing from the spirit and scope of the invention.)

As shown in FIG. **8A**, fabrication of the top **260** and upper bottom **264** is nominally identical, although top **260** may utilize a thicker wafer than upper bottom **264** (e.g., about 1000+/-5 μm , and 500+/-5 μm , respectively). Fabrication of each of these layers begins with a wafer **250**, followed by growth of an oxide layer **252** to protect the wafers for future fusion wafer bonding. Alignment marks **254** are transferred to opposite sides of the wafers as discussed hereinabove, followed by deposition of an oxide (SiO_2) mask **256**, which is patterned with a photo-resist **258** and then etched to selectively remove the oxide. The backside of the wafer is then DRIE etched to provide a clearance **257** for springs **228**. The topside is also DRIE etched completely through the wafer to provide gaps at **259** to form cavities **230** (FIG. **7B**).

As shown in FIG. **8B**, middle layer **262** is fabricated substantially as described with respect to FIG. **8A**, though without clearance **257**, and with gaps **259'** of smaller transverse dimension than gaps **259**, to form fingers **228** (FIG. **7B**). As shown in FIG. **8C**, lower bottom layer **266** is fabricated substantially as described with respect to FIGS. **8A & 8B**, though without clearance **257**, and with a single, relatively large gap **259''** to form abutment (ledge) **234** (FIGS. **7B, 8D**). Using alignment marks **254**, the four layers **260, 262, 264** and **266** are aligned with one another and then bonded to one another to form the completed assembly **220** as shown in FIG. **8D**.

The following illustrative examples are intended to demonstrate certain aspects of the present invention. It is to be understood that these examples should not be construed as limiting.

EXAMPLES

Example 1

Generalized grid **126** and electrode **122** assemblies were fabricated substantially and shown and described hereinabove with respect to FIGS. **1-6**, as microfabricated MEMS assemblies **120** fabricated from 650 μm thick silicon wafers. Grid **126** had a meso-scale transverse dimension D_1 of about 3 cm, and grid support **122** had a meso-scale transverse dimension D_2 of about 5 cm. Fingers **128** had a length of about 1.09 cm and a uniform width of about 550 μm . Other, similar examples were fabricated with fingers having tapered maximum widths of 700 μm and 1000 μm , respectively. The assemblies had an initial loose-fitting alignment (FIG. **4A**) having clearance of about 0.5 mm, and an intermediate clearance (FIG. **4B**) of about 50 μm . The components were successfully hand assembled, with resulting alignment accuracy within 8 micrometers standard deviation.

Example 2

Generalized grid **126** and electrode **122** assemblies were fabricated substantially as set forth in Example 1, though the grid was fabricated from polyimide using an excimer laser cutter. The components were successfully hand assembled to an alignment accuracy similar to that of Example 1, thus demonstrating the ability of these embodiments to enable the precise hand assembly of components microfabricated from mutually distinct materials.

Example 3

Generalized rod **226** and support **222** assemblies were fabricated substantially and shown and described herein-

11

above with respect to FIGS. 7A-8D, as microfabricated MEMS assemblies 220. The supports 222 were fabricated from 500 and 1000 μm thick silicon wafers. Rods 226 were fabricated from stainless steel, and had a meso-scale longitudinal dimension of about 1.5 cm, and a diameter of about 0.5 mm. The support 222 had a meso-scale transverse dimension D_1 of about 0.8 cm. Fingers 128 had moment arm lengths of about 0.5 cm and a uniform width within a range of about 300-500 μm . The assemblies had an initial loose-fitting alignment having clearance sufficient to enable assembly with hand tools, with resulting assembled alignment accuracy within about 5 μm . This example also demonstrates the ability of these embodiments to enable the precise hand assembly of components microfabricated from mutually distinct materials.

In the preceding specification, the invention has been described with reference to specific exemplary embodiments thereof. It will be evident that various modifications and changes may be made thereunto without departing from the broader spirit and scope of the invention as set forth in the claims that follow. The specification and drawings are accordingly to be regarded in an illustrative rather than restrictive sense.

Having thus described the invention, what is claimed is:

1. A hand assembled MEMS apparatus comprising:
 - a meso-scale first component;
 - a meso-scale second component;
 - at least one of said first and second components being a microfabricated MEMS device having a plurality of spring members co-located on a single wafer substrate; said first and second components adapted for being moved by hand relative to one another in an assembly direction, from a relatively loose-fit preliminary alignment orientation to a relatively tight-fit assembled orientation;
 - said spring members configured to bias an other of said first and second components towards the assembled orientation;
 - at least one cam surface integrally disposed on the other of said first and second components, said cam surface configured to slidably engage and move said spring members against their biases upon continued hand movement in the assembly direction;
 - a microfabricated abutment disposed on at least one of said first and second components, said abutment disposed to limit relative movement of said first and second components in at least one direction other than the assembly direction;
 - said spring members configured to move independently of said abutment, wherein said abutment is configured to limit deflection of the spring members by the other of said first and second components; and
 - a microfabricated tactile feedback member disposed on at least one of said first and second components, said tactile feedback member configured to disrupt the hand movement in the assembly direction once said components have substantially reached said assembled orientation.
2. The apparatus of claim 1, wherein said tactile feedback member comprises a ledge disposed to impede continued movement in the assembly direction.
3. The apparatus of claim 2, wherein said abutment comprises a wall portion configured to restrict relative movement of said first and second components transverse to the assembly direction.
4. The apparatus of claim 3, wherein said wall portion is configured to limit movement of said cam surface generated by the bias of said spring members.

12

5. The apparatus of claim 2, comprising another ledge disposed to restrict movement of said cam surface in a disassembly direction.

6. The apparatus of claim 1, comprising an other cam surface configured to move said components into intermediate alignment upon hand movement in the assembly direction.

7. The apparatus of claim 1, wherein said meso-scale dimension is within a range of:

- at least about 0.5 cm; and
- about 10 cm.

8. The apparatus of claim 1, wherein said cam surface comprises a microfabricated cam surface.

9. The apparatus of claim 1, wherein said at least one cam surface is configured to move in a rotational assembly direction to slidably engage and move said spring members against their biases.

10. The apparatus of claim 1, wherein both of said first and second components are microlithographic.

11. The apparatus of claim 1, wherein said at least one microfabricated abutment comprises a plurality of microlithographic abutments.

12. The apparatus of claim 1, wherein said abutment is disposed to limit movement of said first and second components relative to one another in at least one direction transverse to the assembly direction.

13. The apparatus of claim 1, wherein said abutment is disposed to limit movement of said first and second components relative to one another in a disassembly direction.

14. The apparatus of claim 1, wherein said tactile feedback member comprises an engagement surface disposed substantially transverse to the assembly direction.

15. The apparatus of claim 1, wherein said tight-fit assembled orientation is one or more orders of magnitude tighter than said loose-fit preliminary alignment orientation.

16. The apparatus of claim 15, wherein said tight-fit assembled orientation comprises alignment within tens of micrometers.

17. A method for fabricating a hand assemblable apparatus, the method comprising:

- (a) providing a meso-scale first component;
- (b) providing a meso-scale second component, wherein at least one of said first and second components is a microfabricated MEMS device having a plurality of spring members co-located on a single wafer substrate;
- (c) adapting the first and second components for being moved by hand relative to one another in an assembly direction, from a relatively loose-fit preliminary alignment orientation to a relatively tight-fit assembled orientation;
- (d) configuring said spring members to bias an other of said first and second components towards the assembled orientation;
- (e) integrally disposing at least one cam surface on the other of said first and second components, said cam surface configured to slidably engage and move said spring members against their biases upon continued hand movement in the assembly direction;
- (f) disposing a microfabricated abutment on at least one of said first and second components, said abutment disposed to limit relative movement of said first and second components in at least one direction other than the assembly direction, wherein said spring members are configured to move independently of said abutment, and said abutment is configured to limit deflection of the spring members by the other of said first and second components; and

13

(g) disposing a microfabricated tactile feedback member on at least one of said first and second components, said tactile feedback member configured to disrupt the hand movement in the assembly direction once said components have substantially reached said assembled orientation. 5

18. The method of claim 17, wherein said tactile feedback member comprises a ledge disposed to impede continued movement in the assembly direction.

19. The method of claim 17, wherein said abutment comprises a wall portion configured to restrict relative movement of said first and second components transverse to the assembly direction. 10

20. The method of claim 19, wherein said wall portion is configured to limit movement of said cam surface generated by the bias of said spring members. 15

21. The method of claim 17, wherein said meso-scale dimension is within a range of:
at least about 0.5 cm; and
about 10 cm. 20

22. The method of claim 17, wherein said cam surface is configured to move in a rotational assembly direction to slidably engage and move said spring members against their biases.

23. The method of claim 17, wherein said abutment is disposed to limit movement of said first and second components relative to one another in at least one direction transverse to the assembly direction. 25

24. The method of claim 17, wherein said abutment is disposed to limit movement of said first and second components relative to one another in a disassembly direction. 30

25. The method of claim 17, wherein said tight-fit assembled orientation is one or more orders of magnitude tighter than said loose-fit preliminary alignment orientation.

26. The method of claim 25, wherein said tight-fit assembled orientation comprises alignment within tens of micrometers. 35

14

27. A hand assembled apparatus comprising:
a microlithographic, meso-scale first component;
a microlithographic, meso-scale second component;
at least one of said first and second components being a MEMS device having a plurality of spring members co-located on a single wafer substrate;

said first and second components adapted for being moved relative to one another in an assembly direction;
said spring members configured to bias the other of said first and second components towards an assembled orientation;

a microlithographic cam surface integrally disposed on the other of said first and second components, said cam surface configured to move in a rotational assembly direction to slidably engage and move said spring members against their biases;

a plurality of microlithographic abutments disposed on at least one of said first and second components, said abutments disposed to limit movement of said first and second components relative to one another in at least one direction other than the rotational assembly direction;

said spring members configured to move independently of said abutment, wherein said abutment is configured to limit deflection of the spring members by the other of said first and second components;

a microlithographic tactile feedback member disposed on at least one of said first and second components, said tactile feedback member configured to disrupt movement in the assembly direction once said components have substantially reached said assembled orientation.

28. The apparatus of claim 1, wherein the spring members are elongated, having:

a moment arm length within a range of about 0.5 to 1.0 cm;
and
a width within a range of about 300 to 1000 μm .

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,900,336 B2
APPLICATION NO. : 11/404676
DATED : March 8, 2011
INVENTOR(S) : Akintunde Ibitayo Akinwande et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 12, Line 45, "water", should read --wafer--.

Signed and Sealed this
Fifth Day of July, 2011

A handwritten signature in black ink that reads "David J. Kappos". The signature is written in a cursive, slightly slanted style.

David J. Kappos
Director of the United States Patent and Trademark Office